Road Specification for Town of Trego
Four Rod Town Right-of-Way

3 ft shoulder 3 ft shoulder
← ---------- 20 ft ---------- →

Requirements:

1. Staking and clearing of right-of-way
    a. removal of trees and brush from entire width of right-of-way
    b. relocation of telephone and/or electrical wires and power poles if applicable
    c. removal of all personal property

2. Salvage of existing topsoil to spread; purchase and application of seed, fertilizer and mulch.

3. Purchase of silt fencing, gravel, and culverts including aprons; installation per town and/or WDNR specifications.

4. Culverts are only to be installed on slopes, and to avoid pooling of water.

5. Adequate ditches to meet specification range and allow proper drainage.

6. Ditch checks purchased and installed on slopes where needed.

7. Gravel specification: WDOT ¾" base aggregate gradation spec.

8. Road width
    a. minimum of 26 ft with a 2% crown
    b. eight inch gravel base compacted to five inches

9. Road surface
    a. 20 ft blacktop
    b. 3 ft gravel shoulder

10. Road may not exceed 6% grade.

11. Dead end roads require a 62 ft cul-du-sac or minimum 60 ft x 50 ft turnaround.

12. All requirements described are minimum standards. Any improvements made shall meet the requirements set forth by the Wisconsin Department Transportations Facilities Development Manual (FDM).

Additional Requirements for Privately Owned Roads:

1. Any private road being turned over to the Town of Trego shall be paved with hot mix asphalt or warm mix asphalt, compacted to a minimum depth of 2 inches.

Adopted by the Trego Town Board the 13th day of August, 2013.